


| SPECIFICATION | CONNECTION | BIPOLAR |
|--|------------|------------|
| AMPS/PHASE | | 1.00 |
| RESISTANCE/PHASE(Ohms)@25°C | | 3.60±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 1.80±20% |
| HOLDING TORQUE(Nm)[lb-in] | | 0.06[0.53] |
| STEP ANGLE(°) | | 1.80±5.00% |
| DYNAMIC AXIAL LOAD(N) | | 2.4 |
| DYNAMIC RADIAL LOAD(N)@SHAFT LENGTH 20 mm | | 5.0 |
| ROTOR INERTIA(g-cm ²) | | - |
| WEIGHT(Kg)[lb] | | 0.80[1.76] |
| RELIABILITY:MTBF 6000 HOURS OR MORE @24/300RPM | | |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -20°C~50°C[-4°F~122°F] | | |
| INSULATION CLASS B 130°C[266°F] | | |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) | | |

| TYPE OF CONNECTION (EXTERN) | | MOTOR | |
|-----------------------------|---------|-------|---------|
| PIN NO | BIPOLAR | LEADS | WINDING |
| 2 | A — | RED | A |
| 1 | A\ — | BLU | A\ |
| 3 | B — | ORG | B |
| 4 | B\ — | YEL | B\ |

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

| STEP | A | B | A\ | B\ | | CCW |
|------|---|---|----|----|---|-----|
| 1 | + | + | - | - | ↓ | ↑ |
| 2 | - | + | + | - | | |
| 3 | - | - | + | + | ↑ | ↓ |
| 4 | + | - | - | + | | |



| | | |
|-------|-----------|----------|
| APVD | | 3.4.2019 |
| CHKD | | |
| 1:1 | DRN | |
| SCALE | SIGNATURE | DATE |

STEPPER MOTOR

24HR04-1004S