

Technical drawing of a mechanical component showing three views: front, side, and top. The front view shows a rectangular plate with a central circular feature and four corner holes. The side view shows the profile of the plate with a central slot. The top view shows the plate with a central circular feature and four corner holes. Dimensions are provided for all views.

Front View Dimensions:

- Overall width: 60
- Overall height: 95
- Central circular feature diameter: $\varnothing 13$
- Four corner holes: 4- $\varnothing 10$
- Four mounting holes: 4-M4
- Dimensions: 52.3, 40, 23.6, 26.5, 4, 31, 50.5, 55, 40

Side View Dimensions:

- Overall width: 51
- Central slot width: 16
- Slot depth: 8.5
- Dimensions: 22, 21.5, 16, 7, 8

Top View Dimensions:

- Overall width: 61
- Overall height: 64
- Central circular feature diameter: $\varnothing 13$
- Four corner holes: 4- $\varnothing 10$
- Four mounting holes: 4-M4
- Dimensions: 17.5, 17.5, 23.8, 23.8, 500 $\pm$ 20

Reduction ratio	$\frac{1}{36}$	$\frac{1}{66}$	$\frac{1}{94}$	$\frac{1}{149}$	$\frac{1}{196}$	$\frac{1}{211}$	$\frac{1}{277}$	$\frac{1}{394}$	$\frac{1}{624}$	$\frac{1}{830}$	$\frac{1}{1166}$
Numberofgeartrans	3			4					5		
Ratedspeed (rpm) at60Hz	77.7	42.4	29.7	18.7	14.2	13.2	10.1	7.1	4.4	3.3	2.4
TT-YJ61-16 L=16 (kgf.cm) Rated torque	3.68	6.74	9.61	13.6	17.8	19.2	25.2	32.5	51.5	68.6	80.0
TT-YJ61-26 L=26 (kgf.cm) Rated torque	5.78	10.6	15.1	21.3	28.0	30.2	39.6	51.1	80.0	80.0	80.0
TT-YJ61-30 L=30 (kgf.cm) Rated torque	7.36	13.5	19.2	27.1	35.7	38.4	50.4	65.1	80.0	80.0	80.0
TT-YJ61-35 L=35 (kgf.cm) Rated torque	9.20	16.9	24.0	33.9	44.6	48.0	63.0	80.0	80.0	80.0	80.0
TT-YJ61-40 L=40 (kgf.cm) Rated torque	10.5	19.3	27.4	38.7	50.9	54.9	72.0	80.0	80.0	80.0	80.0
TT-YJ61-50 L=50 (kgf.cm) Rated torque	13.6	25.1	35.7	50.3	66.2	71.3	80.0	80.0	80.0	80.0	80.0

Voltage can make as customers' request .

CTN size: 41.5X25.5XH12.8cm 10pcs/CTN N.W.13kgs